

FLS-300 Light Source

NETWORK TESTING OPTICAL



The FLS-300 Light Source is part of EXFO's new line of handheld units, which includes the FPM-300 Power Meter and the FOT-300 Optical Loss Test Set.

KEY FEATURES

Multifunctional light source: up to three singlemode wavelengths on a single port, or four wavelengths (two multimode, and two singlemode) on two ports

Power autonomy of 120 hours

Highest output power in the industry

Three-year warranty and recommended calibration interval, for dramatically reduced cost of ownership

Ergonomic, eye-catching handheld package

SPEC SHEET

EXFO

AUTO-WAVELENGTH RECOGNITION

The FLS-300 Light Source can transmit with a wavelength-identification digital encrypted protocol, so that any compatible unit—the FPM-300 Power Meter and the FOT-300 Optical Loss Test Set—can automatically use the proper calibration parameters. This feature reduces the need for communication between the two technicians and decreases the potential for error.

DISTANT REFERENCING


Signal encrypting can also give the receiving end information on the power to be used as reference, helping ensure efficient referencing, even when the two units are far apart.

FTTx READY

EXFO's FLS-300 allows for the testing of passive optical networks (PONs) at 1310 nm, 1490 nm and 1550 nm, the three wavelengths recommended by the ITU-T (G.983.3) for PONs.

| SPECIFICATIONS ^a | | | | |
|---|------------------------|-------------------------------------|-------------------------------------|--------------------------|
| Model ^b | 23BL | 234BL | 235BL | 12D |
| Central wavelength (nm) | 1310 ± 20 1550 ± 20 | 1310 ± 20 1550 ± 20 1625 ± 15 | 1310 ± 20 1490 ± 10 1550 ± 20 | 850 ± 25 1300 +50/-20 |
| Spectral width ^c (nm) | ≤5 | ≤5 | ≤5 | 50/135 |
| Output power (dBm) | ≥1/≥1 | ≥1/≥-3/≥-5 | ≥1/≥-4.5/≥-3 | ≥-20/≥-20 (62.5/125 μm) |
| Power stability ^d (dB) 8 hours | ±0.10 | ±0.10 | ±0.10 | ±0.10 |
| Battery life ^e (hours) | 120 | 100 | 120 | 120 |
| Enables automatic wavelength recognition | Yes | Yes | Yes | Yes |
| Tone generation (Hz) | 270, 1 k, 2 k | 270, 1 k, 2 k | 270, 1 k, 2 k | 270, 1 k, 2 k |
| Warranty and recommended calibration interval (years) | 3 | 3 | 3 | 3 |

| GENERAL SPECIFICATIONS | | |
|-------------------------------|------------------------------------|---|
| Size (H x W x D) | 18.5 cm x 10.0 cm x 5.5 cm | (7¼ in x 4 in x 2¼ in) |
| Connectors | 0.4 kg | (0.9 lb) |
| Temperature operating storage | -10 °C to 50 °C -40 °C to 70 °C | (14 °F to 122 °F) (-40 °F to 158 °F) |
| Relative humidity | 0 % to 95 % non-condensing | |



STANDARD ACCESSORIES

User guide, Certificate of Calibration, instrument stickers in six languages, AC adapter, three AA batteries, wrist strap.

Notes

- a. Guaranteed unless otherwise specified.
- b. All specifications valid at 23 °C ± 1 °C, with an FC connector.
- c. rms for lasers and -3 dB width for LEDs; typical values for LEDs.
- d. After 15 minutes warmup; expressed as ± half the difference between the maximum and minimum values measured during the period, with an APC connector on the power meter.
- e. Typical autonomy in Auto mode.

ORDERING INFORMATION

FLS-300-XX-XX

Model

- FLS-300-12D = 850/1300 nm LED 62.5/125 μm
- FLS-300-23BL = 1310/1550 nm laser 9/125 μm a
- FLS-300-234BL = 1310/1550/1625 nm laser 9/125 μm
- FLS-300-235BL = 1310/1490/1550 nm laser 9/125 μm a
- FLS-300-12D-23BL = 850/1300 nm LED 62.5/125 μm, 1310/1550 nm laser 9/125 μm

Connector

- EI-EUI-28 = UPC/DIN 47256
- EI-EUI-76 = UPC/HMS-10/AG
- EI-EUI-89 = UPC/FC narrow key
- EI-EUI-90 = UPC/ST
- EI-EUI-91 = UPC/SC
- EI-EUI-95 = UPC/E-2000
- EI-EUI-98 = UPC/LC
- EA-EUI-28 = APC/DIN 47256 a
- EA-EUI-89 = APC/FC narrow key a
- EA-EUI-91 = APC/SC
- EA-EUI-95 = APC/E-2000 a
- EI-EUI-98 = APC/LC

Example: FLS-300-234BL-EI-EUI-89

Note

- a. EA-EUI only available on models 23BL and 235BL.

EXFO Headquarters > Tel.: +1 418 683-0211 | Toll-free: +1 800 663-3936 (USA and Canada) | Fax: +1 418 683-2170 | info@EXFO.com | www.EXFO.com

EXFO serves over 2000 customers in more than 100 countries. To find your local office contact details, please go to www.EXFO.com/contact.

EXFO is certified ISO 9001 and attests to the quality of these products. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.

For the most recent version of this spec sheet, please go to the EXFO website at www.EXFO.com/specs.

In case of discrepancy, the web version takes precedence over any printed literature.

